

Secure 4-port, Dual-head DisplayPort KVM switch with dedicated CAC port & 4K Ultra-HD support

KEY FEATURES

- Supports Windows, Mac and Linux OS
- Dual-head DisplayPort video interface
- 4K Ultra-HD resolution - supports up to 3840 x 2160 @ 60Hz
- Advanced configurable CAC port
- External power supply - Level VI efficiency
- Computer interface isolation while powered or unpowered
- Ensures all user data is completely isolated and no data is ever stored
- Optional remote control available via our RCS-100 or STC-100 models
- No external interfaces can be used, only keyboard, mouse and CAC devices accepted
- Secure channel switching with leak prevention, no hotkeys
- Front panel tactile buttons for secure channel switching and LED channel indicators
- Peripheral and authentication ports isolation for secure usage
- Tamper evident label and anti-tampering technology
- No wireless devices connected
- Ensures only trusted admin gains access
- Audio is natively integrated into the DisplayPort (DP) stream. Due to the secure KVM design, the audio component cannot be extracted or routed independently and is handled exclusively as part of the DP stream.

APPLICATIONS

- Government Operations
- Defense Applications
- Secure Control Rooms
- Corporate Communications
- Server Operations
- Educational Administrations
- Medical Facilities
- Banking Network
- Insurance Data Centers
- Transit Management
- Industrial Operation
- Intelligence Communications



KEYBOARD AND MOUSE EMULATION

The Secure KVM emulates (simulates) the presence of a keyboard and mouse for every attached computer through a USB cable. Both selected and non-selected computers maintain a constant connection with the unit's keyboard mouse emulation controllers, allowing for ultra-fast switching and restricting discovery of newly connected peripherals during switching operations. Emulation of keyboard and mouse also prevents direct connection between the peripherals and the connected computers, shielding systems from potential vulnerabilities.

CAC SUPPORT

Many secure KVM switches support CAC devices, such as smart-card and biometric readers, bolstering security when using the device. However, IPGard takes CAC security even further, allowing users to assign specific peripheral devices to the KVM's CAC port. Once a peripheral device has been registered by an authenticated admin, users can then switch the connection between that device and the PC's along with KVM switching.

SECURE VIDEO/AUX EMULATION

The KVM can simulate a generic EDID, allowing it to operate most of the connected DP monitors in the market. Both selected and non-selected computers maintain a constant connection with the unit's video and EDID emulation controllers, allowing for ultra-fast switching and restricting discovery of newly connected monitors during switching operations. The unit prevents unwanted and unsecure data from getting transmitted between the computers and the display.

VIDEO		
Format	DisplayPort1.2a	
Input Interface	(8) DisplayPort	
Output Interface	(2) DisplayPort	
Resolution	720p (1280×720 @60Hz), 1080p (1920×1080 @60Hz), 1440p (2560×1440 @60Hz), and 4K (3840×2160 @60Hz); supports mixed input resolutions from up to 4 hosts in dual-display configurations	
DDC	5 volts p-p (TTL)	
Input Equalization	Automatic	
Input/Output Cable Length	Up to 20 ft.	
Display Protection	Plug-and-Play signal protection and EDID emulation	
USB		
Input Interface	(8) USB Type B	
Output Interface	(2) USB 1.1 Type A for KM Devices	
Emulation	USB 1.1 and USB 2.0 Compatible	
CAC	Configurable USB 2.0 port with unidirectional optical data diodes for secure CAC operation	
AUDIO (analog)		
Audio Input	(4) 3.5mm stereo audio	
Audio Output	(1) 3.5mm stereo audio	
Security	Isolated audio channel with hardware diode protection	
AUDIO (digital)		
Audio Input / Output	Integrated audio passes from DP IN to DP OUT without any possible separation	
CONTROL		
Front Panel	Select buttons with status LED indicators	
RS-232	Control via serial commands @ 115200 bps	
Hotkeys	Keyboard hotkey switching and configuration	
SECURITY & DESIGN		
Chassis	All-metal tamper-resistant design with active chassis intrusion detection (disables device upon breach)	
Packaging	Tamper-evident sealed product packaging	
Data Protection	Unidirectional optical data diodes on USB and video paths to ensure one-way data flow	
Certifications	NIAP PP 4.0, UL, CE, RoHS Compliant, ICES-003	
OTHER		
Power	External 100-240 VAC/ 12VDC3A @ 24W	
Dimensions	12.57" W x 2.7" H x 6.69" D	
Weight	4.2 lbs	
Operating Temp.	+32 to +104°F (0 to +40°C)	
Storage Temp.	-4 to 140°F (-20 to +60°C)	
Humidity	Up to 80% (no condensation)	
ORDERING INFORMATION		
Part No.	UPC	Description
SA-DPN-4D-P	686911124112	4-Port DH Secure Pro DP KVM w/audio and CAC, PP 4.0. Includes: [SA-DPN-4D-P; PS12V3A]